

ZJI single-boot sump entry fittings use a single hole installation with embedded bolts to seal off the containment sump pipe entry. Installation is simple, quick and clean. The RF ECO fitting pairs with **ANY** manufactured containment sump and piping for an easy, "ECO" nomical sump-entry solution. Also available with a UV resistant white design boot.



FEATURES

- Made with *ProTex*, a non-urethane, co-polymer material compatible with all fuel types
- No measurable hydrolysis and naturally anti-microbial for significant durability
- Single hole install with embedded stainless bolts for quick install and maximum seal
- 3rd party tested for compatibility to the UL 2447 requirements
- End-of-sump life warranty

SPECIFICATIONS

FLAT or CURVED SUMP WALL

SMALL

	Conduit & Small Diameter Pipe Applications to 1.6" OD (Small Housing 3.25" Hole)
/	Medium Diameter Pipe Applications to

MEDIUM

3.9" OD (Medium Housing 5.5" Hole)

LARGE Large Diameter Pipe Applications to 5.0" OD (Large Housing 6.625" Hole)

*custom sizes available

COMPONENTS

- Exterior Housing with Embedded Bolts
- 2 Exterior Gasket
- 3 Interior Gasket
- 4 Interior Housing
- 5 Locknuts
- 6 Flexible Boot
- Stainless Steel Clamps





zjiproducts.com

Tel: 844.850.0005 250 N Red Cliffs Drive 4B-236 St George, Utah 84790